Product Name: Wheel Magic 1 gallon Product identifier: 502500 Revision Date: 12-18-2015 Replaces:



1. Identification

Product Name: Product identifier: Relevant identified uses of the substance or mixture and uses advised against:	Wheel Magic 1 gallon 502500 Wheel Cleaner
Other means of identification Chemical Manufacturer / Importer / Distributor: Emergency telephone number:	ITW Evercoat a division of Illinois Tool Works Inc. 1275 Round Table Drive Dallas, TX 75247 CHEMTREC: 1-800-424-9300 CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;



GHS Classification: Skin Corrosion/Irritation Category 1A Serious Eye Damage/Eye Irritation Category 1 Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2 **GHS Signal Word:** Danger **GHS Hazard Statements:** Causes severe skin burns and eye damage. May cause damage to organs through prolonged or repeated exposure. **GHS Precautionary Statements: Safety Precautions:** Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. First Aid Measures: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Product Name: Wheel Magic 1 gallon Product identifier: 502500 Revision Date: 12-18-2015 Replaces:

Storage: Disposal:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor/ Get medical advice/attention if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.
Hazards not otherwise classified:	No data available

3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Sodium hydroxide	1310-73-2	3 - 7
2-propanol-1-butoxy ether	5131-66-8	1 - 5
Tetrasodium Ethylenediamine	64-02-8	0.5 - 1.5
Tetraacetate		
Diethanolamine	111-42-2	0.5 - 1.5

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Eye Contact:	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. This corrosive material can cause immediate and permanent eye damage. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.
Skin Contact:	Wash with soap and water under a drench shower. Remove contaminated clothing, launder immediately, and discard contaminated leather goods. Get medical attention immediately.
Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately
Ingestion:	Corrosive. Do not induce vomiting! Drink one glass of water followed by milk if available. Seek medical attention immediately and give the medical care provider with this MSDS.

Product Name: Wheel Magic 1 gallon
Product identifier: 502500
Revision Date: 12-18-2015
Replaces:

Immediate medical attention No additional first aid information available and special treatment needed,:

5. Fire-fighting measures			
Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do Not direct a stream of water into the hot burning liquid.		
Unsuitable extinguishing media:	No data available		
Fire and/or Explosion Hazards: Hazardous Combustion	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire. Water Reactive. Material will react with water and may release a flammable and/or toxic gas.		
Products:	Carbon dioxide, Carbon monoxide		
Special protective equipment	Do not enter fire area without proper protection including self-		
and precautions for fire-	contained breathing apparatus and full protective equipment. Use		
fighters:	methods for the surrounding fire.		
6. Accidental release measures			
Personal precautions,	Exposure to the spilled material may be severely irritating or toxic.		
protective equipment and	Follow personal protective equipment recommendations found in		
emergency procedures:	Section VIII of this MSDS. Personal protective equipment needs		
Methods and material for containment and cleaning up:	must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.		
7. Handling and storage			
Precautions for safe handling:	Toxic or severely irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area.		
Conditions for safe storage: Materials to Avoid/Chemical Incompatibility::	Store in a cool dry place. Isolate from incompatible materials. Strong oxidizing agents Acids Metals Water Organic halides Copper Copper alloys Strong acids Metals (ferrous)		

Product Name: Wheel Magic 1 gallon Product identifier: 502500 Revision Date: 12-18-2015 Replaces:

8. Exposure controls/personal protection

Limits:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Sodium hydroxide	2 mg/m3	2 mg/m3	No data available
Diethanolamine	No data available	2 mg/m3	No data available
Appropriate engineering controls.:	Local exhaust ventilation, process enclosures, or other engineering controls are necessary when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits Engineering controls must be designed to control vapor concentrations to below levels published in 29 CFR 1910.1000. Facilities storing or using this material should be equipped with an eyewash and safety shower.		
Eye Protection:	Wear chemical splash goggles when handling this product. Additionally, wear a face shield when the possibility of splashing of liquid exists. Do not wear contact lenses. Have an eye wash station available. Wear goggles and a Face shield		
Skin Protection:	Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield		
Respiratory Protection:	Respiratory protection must be used when handling this product. Use respirators only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. A supplied air type respirator may be required. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator. Wear a NIOSH approved respirator if any exposure is possible.		
Other Protective Equipment:	0 00	eld Where contact is likely, we chemical suit, rubber boots, an a face shield	

Product Name: Wheel Magic 1 gallon Product identifier: 502500 Revision Date: 12-18-2015 Replaces:

9. Physical and chemical properties

Appearance (physical state):	Liquid
Color:	Clear
Odor:	Aromatic
Odor threshold:	No data available
pH:	>12.5
Melting Point/Freezing Point (°C):	No data available
Initial Boiling Point and Boiling Range (°C):	100
Flash Point (°C):	100
Evaporation Rate:	No data available
Flammability (solid, gas):	No data available
Upper Flammable/Explosive Limit:	No data available
Lower Flammable/Explosive Limit:	No data available
Vapor Pressure:	17.5 MMHG@20C/68F 1 MMHG@20C/68F
Vapor Density:	No data available
Relative Density:	1.06
Relative Density:	1.06
Solubility(ies):	Will mix with water
Partition coefficient: n-octanol/water:	No data available
Auto-ignition Temperature (°C):	662 °C
Decomposition Temperature::	No data available
Viscosity:	352

10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under normal conditions.
Conditions to avoid:	None known. Contamination Contact with water.
Incompatible materials:	Strong oxidizing agents Acids Metals Water Organic halides Copper
	Copper alloys Strong acids Metals (ferrous)

11. Toxicological information

Likely routes of exposure (inhalation, ingestion, skin and eye contact):	Inhalation, Ingestion, Skin contact, Eye contact
Immediate (Acute) Health Effects	by Route of Exposure:
Inhalation Irritation:	Can be corrosive to the respiratory tract causing severe irritation and tissue damage.
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs)
Skin Contact:	Corrosive to skin tissue. Can cause chemical burns. Corrosive, causes skin burns and permanent skin damage (scarring).
Skin Absorption:	Minimal hazard in normal industrial use. May cause gastrointestinal discomfort

Eye Contact:	Corrosive to eye tissue. Can cause severe irritation, tearing, and burns that can
,	quickly lead to permanent injury including blindness. Corrosive. Will cause eye burns and permanent tissue damage.
Ingestion Irritation:	Corrosive to tissue. Can cause severe and permanent damage to mouth, throat,
	stomach. Aspiration may lead to lung damage. Corrosive to tissue. Can cause severe
	and permanent damage to mouth, throat, stomach. Aspiration may lead to lung damage.
Ingestion Toxicity:	Harmful if swallowed. May cause systemic poisoning.
Long-Term (Chronic) Health Ef	ífects:
Carcinogenicity:	None of the substances have been shown to cause cancer in long term animal studies. Not a carcinogen according to NTP, IARC, or OSHA. Cancer hazard! Contains a material that can cause cancer.
Reproductive and	No data available to indicate product or any components present at greater than
Developmental Toxicity:	0.1% may cause birth defects.
Mutagenicity:	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
Inhalation:	Upon prolonged and/or repeated exposure, can be corrosive to the respiratory tract causing severe irritation and tissue damage. Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs)
Skin Contact:	Upon prolonged or repeated contact, corrosive to skin tissue. Can cause chemical burns.
Skin Absorption:	Upon prolonged or repeated exposure, minimal hazard in normal industrial use. May cause gastrointestinal discomfort.

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
No data available			

Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No data available			

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):	Harmful to aquatic life.
Persistence and degradability:	No data available
Mobility in soil:	No data available
Other adverse effects (such as	No data available
hazardous to the ozone layer):	

Données sur l'écotoxicité				
Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish	
No data available				
13. Disposal considerations				
Description of waste residues	: Spent or discarded waste.	Spent or discarded material is not expected to be a hazardous waste.		
Waste treatment methods (including packaging):	Dispose of in a land	Dispose of in a landfill. Disposal is not likely to be regulated.		
14. Transport information				
UN number:	UN1719			
UN proper shipping name:				
Transport hazard class(es):	8			
Packing group:	III			

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

15. Regulatory information		

Statut TSCA:

All components in this product are on the TSCA Inventory.

Regulated Components:

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Sodium hydroxide	1310-73-2	Ν	Ν	Y	Ν
Diethanolamine	111-42-2	Ν	Ν	Y	Y

16. Other information, including date of preparation or last revision.

Revision Date:	12-18-2015
Revision Number:	6

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use,

Product Name: Wheel Magic 1 gallon Product identifier: 502500 Revision Date: 12-18-2015 Replaces:

recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances